

PROFISTATIC

ROPE



ZPR150 ZPR110

The Profistatic rope is suitable for rescue, evacuation, speleoalpinism and canyoning.

Profistatic ropes have a robust, thicker braid structure suitable for intensive use and maximum safety.

RATING:

LIFESPAN: 10 Years

CERTIFICATION:

EN1891:1998 Type A

EN 1891:1998 Personal protective equipment for the prevention of falls from a height. Low stretch kernmantel ropes



MODEL	SIZE	STANDARDS
ZPR150	10.5mm	EN1891 TYPE A
ZPR110	11mm	EN1891 TYPE A

PRODUCT MAKE	CODE	DIAMETER (MM)	BREAKING LOAD	WEIGHT	NUMBER OF FALLS	IMPACT FORCE	STATIC ELONGATION (%)	DYNAMIC ELONGATION (%)	SHEATH PERCENTAGE (%)	SHRINKAGE (%)	SUPPLENESS
PROFISTATIC 10.5mm	ZPR150	10.5	32KN	65.8g/m	12	5.9kN	3.4	37	.	-3.8	0.7
PROFISTATIC 11mm	ZPR110	11	37KN	77.9g/m	24	5.9kN	3.1	39	.	-4.6	0.7

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
10 Holt Place, Harewood,
Christchurch 8053, New Zealand
sales.nz@zeroheightsafety.com

EUROPE & UK
Badenerstrasse 122,
5466 Kaiserstuhl, Switzerland
sales.eu@zeroheightsafety.com

zeroheightsafety.com

