

ALUBEAM PRO

RAIL/BEAM ANCHOR CLAMP

AAPO0XM

Temporary anchorage point for horizontal or overhead use. Clamps to permanent structural I beam. To be used in conjunction with a fall arrest system and shock absorbing lanyard or a self retracting lifeline for fall arrest or with a positioning lanyard for fall restraint. Quick sliding mechanism to clamp to a range of flange sizes.

RATING: 23kN

LIFESPAN: 10 Years

CERTIFICATION: EN795:1996

EN 795:2012 Personal fall protection equipment. Anchor devices



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
		1900g	490x200mm	Aluminium Alloy	23kN

PRODUCT FEATURES

- Multi-directional anchor ring swivels to point of gravity.
- Clamps to any I beam flange with a minimum width of 100mm and maximum width of 380mm, up to 38mm thickness.
- Click lock action for best fit, with locator pins to secure once clamped.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
10 Holt Place,
Harewood, Christchurch 8053
New Zealand
sales.nz@zeroheightsafety.com

EUROPE & UK
Badenerstrasse 122
5466 Kaiserstuhl,
Switzerland
sales.eu@zeroheightsafety.com

