



CLIMBS

DOUBLE WEBBING LANYARD WITH SNAPHOOK AND SCAFFOLD HOOKS

LCZ2W5E/015

Designed for passing intermediate anchor points on fixed protection, and safe attachment when climbing fixed access ladders or steps. Twin legs ensure the worker remains attached at all times whilst moving from one anchorage to another.

RATING: 100kg

LIFESPAN: 10 Years

CERTIFICATION: EN 355:2002, AS/NZS 1891.1:2007

EN 355:2002 Personal protective equipment against falls from a height. Energy absorbers

AS/NZS 1891.1:2007 Harnesses and ancillary equipment



SMK40523



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
LCZ2W5E/015	0.9m 1.5m		0.9m 1.5m	Polyamide 100%	100kg

PRODUCT FEATURES

- Elasticated webbing lanyard with snaphook at the harness end, and scaffhooks to the anchorage points
- Total length is 1.5m (or 0.9m) to reduce the fall factor.
- The shock absorber will tear to absorb the energy in the event of a fall.
- Stay safe at all times with a double lanyard (twin tail) for continuous attachment to anchor climbing ladder, pylons and rigging to provide a fool-proof fall arrest system.
- The shock absorber end connects to the fall arrest point on the harness.
- The yellow cover can be opened to inspect the shock absorber and labels. Protect the shock absorber from environmental damage, keep closed when using lanyard.
- Also available in 0.9m version, BW-260/0.9.
- Snaphooks and Scaffhooks rated to 20kN
- Permitted to work in potentially explosive areas.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
10 Holt Place,
Harewood, Christchurch 8053
New Zealand
sales.nz@zeroheightsafety.com

EUROPE & UK
Badenerstrasse 122
5466 Kaiserstuhl,
Switzerland
sales.eu@zeroheightsafety.com

