



SUPALITE

RETRACTABLE WEBBING LANYARD 2.4M

LSRZ0W3(SNAPHOOK)

LSRZ0W5(SCAFFHOOK)

Retracting personal lanyard, a fall arrester device with rugged case. Lightweight and compact, ideal for many light duty applications such as static lines, plant maintenance and EWP's. Complete with attachment and swivel.

RATING: 140kg

LIFESPAN: 10 Years

CERTIFICATION: EN 360, AS/NZS 1891.3

EN 360:2002 Personal protective equipment against falls from a height. Retractable type fall arresters

AS/NZS 1891.3:1997 Fall-arrest devices



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
LSRZ0W3	2.4m	1.2kg 1.6kg		Textile webbing	140kg

PRODUCT FEATURES

- Working webbing 17mm, includes integral energy absorber.
- Static Strength: not less than 15kN, arrest force less than 6kN.
- Suitable for horizontal use, maximum deflection from normal: 40 degrees.
- Do not use where a fall could occur over sharp edge.
- With snaphook (WR-025) or scaffhook (WR-027).
- Operating temperature range: -40 to +60 degrees C.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
10 Holt Place,
Harewood, Christchurch 8053
New Zealand
sales.nz@zeroheightsafety.com

EUROPE & UK
Badenerstrasse 122
5466 Kaiserstuhl,
Switzerland
sales.eu@zeroheightsafety.com