



STRETCH

SINGLE ELASTICATED LANYARD

LSZ0W3E(SNAPHOOK)

LSZ0W5E(SCAFFHOOK)

An essential item for any height safety kit. Elasticated webbing lanyard with snaphooks (ABM-T3E) or scaffoldhook (ABM-T5E). European quality.

RATING: 100kg

LIFESPAN: 10 Years

CERTIFICATION: EN 355:2002, AS/NZS 1891.1:2007

EN 354:2010 Personal fall protection equipment. Lanyards

EN 355:2002 Personal protective equipment against falls from a height. Energy absorbers

AS/NZS 1891.1:2007 Harnesses and ancillary equipment



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
LSZ0W3E (Snaphook) LSZ0W5E (Scaffhook)	2m		2M length	Polyamide 100%	100kg

PRODUCT FEATURES

- Total extended length is 2m, with the elastic cover helping to reduce slack which could become a trip hazard.
- Includes shock absorber. The shock absorber will tear to absorb the energy in the event of a fall.
- Standard simple lanyard for attachment to anchor points, providing safe fall arrest system.
- Shock absorber end connects to the fall arrest point on the harness.
- Snaphook and scaffoldhooks rated to 20kN.
- Range of other hardware options available.
- The yellow cover can be opened to inspect the shock absorber and labels. Protect the shock absorber from environmental damage, keep closed when using lanyard.
- Permitted to work in potentially explosive areas.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
10 Holt Place,
Harewood, Christchurch 8053
New Zealand
sales.nz@zeroheightsafety.com

EUROPE & UK
Badenerstrasse 122
5466 Kaiserstuhl,
Switzerland
sales.eu@zeroheightsafety.com

