



## TRADEMATE

SINGLE ADJUSTABLE WEBBING LANYARD

LTZ0WX3(SNAPHOOK)

LTZ0WX5(SCAFFHOOK)

Remove the risk of falls with a shortened lanyard. Ideal for working in fall restraint. Recommended for Elevated work Platforms. Includes shock absorber. Adjustable length from 1.2m to

**RATING:** 100kg

**LIFESPAN:** 10 Years

**CERTIFICATION:** EN 355:2002, AS/NZS 1891.1:2007

EN 354:2010 Personal fall protection equipment. Lanyards

EN 355:2002 Personal protective equipment against falls from a height. Energy absorbers

AS/NZS 1891.1:2007 Harnesses and ancillary equipment



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
LTZ0WX3 (SnapHook) LTZ0WX5 (Scaffhook)			1.2M-2M	Polyamide 100%	100kg

### PRODUCT FEATURES

- Total extended length is 2m, can be shortened to 1.2m to reduce the fall distance.
- The shock absorber will tear to absorb the energy in the event of a fall.
- Standard simple lanyard for attachment to anchorages, scaffolding, EWP's, fall arrest systems
- Shock absorber end connects to the fall arrest point on the harness.
- Snaphooks and scaffhook rated to 20kN.
- Material Polyamide 100%.
- Do not remove the yellow cover as this protects the shock absorber from environmental damage.
- The yellow cover can be opened to inspect the shock absorber and labels. Protect the shock absorber from environmental damage, keep closed when using lanyard.
- Permitted to work in potentially explosive areas.

#### ZERO HEIGHT SAFETY LIMITED

**AUSTRALASIA**  
10 Holt Place,  
Harewood, Christchurch 8053  
New Zealand  
sales.nz@zeroheightsafety.com

**EUROPE & UK**  
Badenerstrasse 122  
5466 Kaiserstuhl,  
Switzerland  
sales.eu@zeroheightsafety.com

